Biodetection & Evaluation of Sensor Placement Using Computational Fluid Dynamics & Machine Learning

Corbet Elkins^a, Japleen Kaur^a, Louis Gonzalez^a, Aaron Shih^a, Sachit Chopra^a, Andrew Matas PhD^b, and David Glasbrenner PhD^b ^aThe Data Mine, Purdue University, West Lafayette, IN ^bBattelle, Columbus, OH

INTRODUCTION

The tracking and detection of pathogen containing biological Our team used CONTAM to simulate and demonstrate the aerosols and contaminants is of great interest for public safety effects of contaminant releases and gain detailed data from the (bioterrorism) and health (pharmaceutical manufacturing. With simulated sensors. CFD0 Editor, a complimentary software improvements in computational power, we were able to to CONTAM, was used to visualize the spatial distribution of the simulate airflow and contamination levels with an open-source aerosol contaminants. computational fluid dynamics (CFD) program known as **Anomaly Detector** CONTAM. Using Python, we built machine learning models to determine the best placement of contaminant sensors in 2D and 3D simulated spaces with virtual biological aerosol sensors with different responses to detect biological threat release (e.g. ഷ bacteria, fungi, spores).



Fig 1. Diagram of modeling approach and optimization of sensor placement

www.battelle.org

RESEARCH METHODOLOGY



The Battelle biodetection team developed a python parser that rapidly parses and exports simulation data as a .csv file. Virtual biological aerosol detectors using from the simulated data was also written in python. The tools and workflow developed by this team provide the necessary foundation for the later stages of this project which include building a deep learning model to evaluate sensor placements.



Fig 2. Diagram of CFD modeling and biodetection event

We then parsed the data from the simulation into .csv files using Python. The data was then used in conjunction with sensor response functions to simulate the signal of a detected aerosol particulate. Additionally, to determine whether an anomalous event occurred, or spike in aerosol concentration, a sliding average z-score "detector" was scripted and used to detect if an event with a z-score greater than or equal to 10 occurred.

We would like to thank our TA Sachit Chopra for his guidance and management of this project. We would especially like to thank Dr. David Glasbrenner and Dr. Andrew Matas, our corporate partners at Battelle, for their guidance and for giving us the opportunity to work on this project.



The Data Mine

CONCLUSION

FUTURE GOALS

Generate simulation data which include simulation of aerosols with virtual occupants and pressure changes over time

Building a deep learning model to predict to predict the optimal placement of multiple sensors in a given space or building

Write a .NET software package with all the tools that have been described for ease of use

Fig 3. Scheme of general neural network architecture

ACKNOWLEDGEMENTS

